



“ROLLED WAVE CLUTCH”



Create a simple yet stunning clutch to match your favorite outfit. This clutch features a contrasting stripe accented by a three thread rolled wave stitch in decorative serger threads and a silk rose for trim.

Skill Level: Beginner

Created by: Kelly Laws, Marketing Project Manager

Supplies:

Baby Lock Sewing Machine

Baby Lock New Evolve featuring the Wave stitch.

Or Baby Lock Imagine Wave and Baby Lock Cover Stitch machine

$\frac{3}{4}$ " Belt Loop Binder (BLE8-S12)

Baby Lock Fusible Firm Flex stabilizer

$\frac{1}{4}$ yard brown satin fabric

7" brown zipper

12" of 1" wide green ribbon or strip of satin fabric

Silk rose for trim

Decorative serger thread in brown and green

4 Spools brown Maxi-Lock thread

$\frac{1}{4}$ lining fabric

Iron and Ironing board

Pattern template (below)

Hand sewing needle

Instructions:

1. Using the pattern template cut the following:
 - 2 pieces of brown satin
 - 2 pieces of fusible firm flex
 - 2 pieces of lining fabric
2. Fuse the satin to one side and the lining fabric to the other side of the firm flex stabilizer
3. Set up the serger for a four thread stitch and serge all four edges of both pieces.
4. Set up the serger for a three thread rolled wave stitch and place the decorative thread in the upper and lower looper.
5. Serge the rolled wave stitch along both edges of the 1" ribbon.
6. Thread the machine with thread to match the ribbon or monofilament thread and set it for a straight stitch.
7. Position the ribbon along one side of the clutch sides using the guidelines on the pattern template for placement reference.
8. Topstitch to secure the ribbon to the clutch side.
9. Thread the machine and set it up for a basting stitch.
10. With right sides together baste the 5/8" seam across the top.
11. Press the seam open.
12. Topstitch the zipper in place.
13. To make the wrist strap cut a strip of the brown satin 1" x 18". Set the Evolve for a wide cover stitch and attach the belt loop binder.
14. Feed the strip into the belt loop binder and serge.
15. Fold the pieces right side together so the wrong sides are facing out.
16. Stitch along the side seam and along the lower edge.
17. Insert the strap so the loop will face the right side of the clutch and the strap will be on the same side as the zipper tab when the zipper is closed.
18. Open the zipper partially. Stitch the lower edge or remaining seam closed
19. Turn the bag right side out through the zipper.
20. Using a hand needle and thread attach the rose trim.

For other exciting projects like this one, visit our Web site at www.babylock.com

Purse template

10 1/4" wide and 6" high

