

BABY LOCK SEWING ACCESSORIES

Pearl & Piping Foot

(ESG-PP)

Instructions

Don't let the name fool you! The Baby Lock Pearl and Piping Foot has many uses such as sewing seams in knitwear, attaching beads up to 4mm, and making and applying piping up to 1/4" in diameter.

Sewing Knitwear:

When you are sewing seams in knitwear such as polar fleece, sweatshirt fleece or French terrycloth, choose one of the overcast or overlock stitches. Guide the edge of the fabric in the tunnel on the bottom of the presser foot.

Note: When cutting out your garment, be sure to cut the seam allowances to 1/4".

Attaching Beads:

To attach beads, select a zigzag wide enough to clear the beads. The width of the zigzag should be set the same as the diameter of the beads. Use a matching or monofilament thread to hold the beads to your work. We recommend reducing the pressure on the presser foot to keep the beads from dragging and creating puckers in the fabric.

Inserting Piping:

Piping can be made for finishing detail on projects ranging from home decorating to the finest heirloom garments. Cover a cotton cord with a bias cut piece of fabric. Sew using a straight stitch close to the cord to hold in place. When inserting the piping into a seam, use this same foot and guide the piping in the opening of the foot, placing the needle as close to the cord as possible. Place your needle in the left position and move the needle to the right using the width control.



FOR THE LOVE OF SEWING