



Paper Pieced Elephant Quilt



This adorable elephant quilt is sure to be the center of attraction in your home. Using your paper piecing skills and your Baby Lock sewing machine as your tool you are sure to have fun creating this project. After you have completed piecing the quilt, take it to the Baby Lock Tiara Quilting machine where you can quilt like a pro.

Size: 30" x 20"

Skill Level: Intermediate

Created by: Diane Kron, Sewing Project Manager

Supplies:

Baby Lock® Tiara Quilting Machine

Baby Lock sewing machine

The Elephant and I Quilt and Pillow Pattern by Jennifer Sampou for Stash

1 Yard each of an assorted group of fabrics from Mary Fons India Collection

Backing fabric

Madeira® Cotona thread for piecing

Madeira Quilting Thread

Batting

Machingers Quilting gloves

Fusible web

Rotary cutter and mat

¼" Straight edge ruler for quilting

Temporary spray adhesive

Basic sewing supplies

Instructions:

1. Read all of the pattern directions before you begin the project. Follow the directions from the pattern for the (elephant only) starting on Page 7. Tip: When you are instructed to press, first press the pieced unit flat to set the seam. Then open the patch, pressing from the front. You may want to reduce or eliminate the use of steam for pressing these papers pieced blocks. Steams tend to curl the patterns.
2. Cut one section for the background of the elephant that measures 26 ½" x 16 ½".
3. Apply the fusible web to the backside of the elephant while following the manufacturer's directions.
4. Center the elephant onto the background section and press.
5. Appliqué the elephant onto the background fabric using your favorite appliqué stitch. In the sample, a satin stitch was used.
6. Cut 4 2" wide strips across the width of the fabric for the sashing.
7. Sew the strips to the top and bottom edges. Then sew two strips to the sides.
8. Make a sandwich with the backing fabric, batting and ending with the elephant section.
9. To hold the sections together during quilting, lightly spray between the layers with the temporary spray adhesive.
10. Set up the Tiara for quilting:
 - Place a drop of oil in the bobbin case.
 - Wind a couple of bobbins with the same thread that will be used for quilting.
 - Place the bobbin in the bobbin case.
 - Thread the machine.
 - Have the ¼" straight edge quilting ruler close to the Tiara.
 - Adjust the tensions as needed.
11. Slide the gloves on your hands. These will help you to move and manipulate the quilt easily during the quilting process.

12. Quilt the elephant first using the straight edge quilting ruler. Rest the edge of the ruler next to the foot on the Tiara. The first row of stitches should be placed in the ditch, use the edge of the foot and the ruler to channel quilt the surface of the elephant. Move the ruler a ¼" away from the first line of stitching and continue on with the quilting process.
13. Free motion quilt around the elephant to finish the quilting process. In the sample, a stippling stitch was used.
14. Trim the edges around the quilt so that the quilt is square.

Binding:

1. Cut several 2 1/2" strips across the width of the white fabric for the binding. Piece the sections together to form one long continuous strip.
2. Fold the wrong sides together along the long edge and press.
3. On one of the short ends, fold in at a 45° angle and press.
4. Place the raw edge of the binding along the outer edge of the quilt starting 6" from the top corner and pin in place.
5. Using a 1/4" seam allowance, start to sew 4" from the top edge of the binding, and continue down the first side of the quilt. Stop when you are ¼" from the corner and backstitch. Cut the thread.
6. Remove the quilt from the machine. Fold the binding up and then down over the second side of the quilt so that the raw edges are even. This will create a 45° corner. Pin in place and sew the second side of the quilt. Stop 1/4" from the second corner; backstitch and cut the thread.
7. Follow the above Binding Steps to finish sewing the binding on the remaining sides of the quilt. When you turn the last corner, trim the end on the binding so that it overlaps past the starting point on the binding. Tuck the binding inside the beginning point of the binding and sew in place.
8. Press the binding to the back of the quilt.
9. To finish your quilt, hand-sew the binding to the backside of the quilt.



For other exciting projects like this one, visit Baby lock at www.babylock.com.



**GET CONNECTED
WITH E-NEWS**

Sign up to get the latest promotions,
new product scoop, sewing tips and
free projects. ▶

Your Email Could Use A Little Embroider-E.

Subscribe to the only e-news devoted
to embroidery software today!

[Subscribe](#)



©2018 Baby Lock USA. This project may be freely used by individuals for non-commercial purposes. Project instructions may not be sold or distributed without approval from Baby Lock. Baby Lock must be acknowledged as the source of the project instructions through copyright or online link