



LEARN & CREATE

with Baby Lock

Summery Serged Pintucked Table Runner



This bright and colorful table runner will add a touch of summer to any table! It comes together in a snap because it can be made completely on a serger. Use different stitches, like the rolled edge and flatlock, to create a unique and fun home décor piece to your dining room or picnic table!

Skill Level: Intermediate

Created by: Diane Kron

Supplies:

Baby Lock® Acclaim Serger

2 Yards of beige home decorator fabric

6 Assorted sections of cotton prints for center and for the strips on the ends

1 ½ yards of coordinating fabric for the backing

Madeira® serging thread colors to coordinate with fabrics

2 Spools YLI variegated Jeans Stitch Thread

Frixion marking pens

3 ½" x 24" straight edge ruler

Rotary cutter and mat

Large eyed needle


Seam sealant

Basic sewing and serging supplies

Instructions:

Finished Size: 12 ½" x 50"

- 1) Follow the next set of cutting directions to cut the fabric needed for the table runner:
 - a) From the home decorator fabric, cut one section that measures 13 ½" x 42".
 - b) From the cotton prints fabrics, cut four strips each from the six different prints 1" x 15". These will be serged to each end of the table runner.
 - c) Fussy cut one section that measures 10" x 13 ½". This section will be serged to the center of the table runner. I found a large floral print fabric that worked nicely.
 - d) Cut one section from the coordinating print fabric that measures 13 ½" x 51" for the backing.
- 2) Using the 13 ½" x 42" home decorator fold the section in half and crease to determine the center.
- 3) On both sides of the center crease, measure outward 6". Draw a straight line using the Frixion pen on both sides. From the first drawn lines measure 1 ½" and draw another straight line across the width of the runner. Repeat until you have five lines drawn on both sides of the center creased line. These will be the lines where the pintucks will be serged.



- 4) Set up the Acclaim serger for a 3-Thread Rolled Edge Stitch. Thread the machine using two spools of YLI variegated Jeans Stitch thread in the loopers and one spool of Madeira thread that coordinates with the fabrics for the needle. In the sample, purple thread was used. Set the Stitch Width to 3.5. Lock the blade in the down position. Do a test serge to be sure that is the look that you would like to achieve using a scrape piece of fabric.
- 5) To create the first pintuck on the runner, fold wrong sides together along the drawn line and finger crease. Place the crease line so that the folded edge runs along the right edge of the foot. Serge along that line. Repeat for the other nine drawn lines.
- 6) On each of the ends on the runner, cut 3" off at a 45° angle as shown below. Use the markings on the ruler along with the cutting mat as your guide.



- 7) To piece together the strips to each of the angled cut ends, place the first 1" wide strips to one angled ends. Clip the strip to secure.
- 8) Set up the Baby Lock Acclaim serger up for 3-Thread Overlock Narrow. Thread the machine with 3 spools of beige thread. Set the width to 3.0 and the stitch length to 3.5. Serge the first strip to the runner. Remove the clips as you serge. Place another 1" strip on the other angled edge. Rotating back and forth until the first end is completed and you have serged five different strips to each side. Trim the ends so that you maintain the 45° angle and the sides are even with the runner. Repeat for the opposite side of the runner.



- 9) Clip the center focus fabric to the center of the table runner centered between the pintucks (as shown below in the illustration).



- 10) Set up the serger for a 2-Thread Flatlock- Wide Stitch. Set the width to 7.5 and the length to 2.0. Set the Blade to the locked position and with the Subsidiary Loper engaged into the left position. Thread the Upper Loper with the YLI thread and the Lower Loper with the Madeira purple serger thread.
- 11) Serge the two side edges to the runner.
- 12) Trim away the edges on the cotton fabric even with the edges on the runner.
- 13) To finish the runner, set up the serger for 3-Thread Overlock Wide.
- 14) Press the front of the runner and the backing fabric.
- 15) Place the backing fabric; wrong side up on a flat surface. Place the front side of the runner facing up over the backing fabric. Clip the two sections together.
- 16) Serge around the outer edge of the runner.
- 17) Thread the ends of the thread, using a big eyed needle under the serged seam on the backside of the runner. This will secure the ends so that they don't unravel. Or you can also use a seam sealant to secure the ends.

For other exciting projects like this one, visit Baby Lock at www.babylock.com.

©2018 Baby Lock USA. This project may be freely used by individuals for non-commercial purposes. Project instructions may not be sold or distributed without approval from Baby Lock. Baby Lock must be acknowledged as the source of the project instructions through copyright or online link